



# EV CHARGER

Shaping Sustainability





- Integrated with different uses of sockets
- Wall-mounted available
- Winner of the Red Dot Design Award
- Compatible with various industrial and household plugs

Specifications	
Product model	D2E-B3P16A
Product power	3.6/11KW
Working current	16A
Working voltage	230V single-phase /400V three-phase
Installation mode	Integrated gun and pile design, with a wall mount bracket provided.
Working altitude	<2000m
Working frequency	50HZ/60HZ
Cable length	7m
Reservation function	2H/4H/6H/8H
Charging method	Plug-and-charge
Operating temperature	-30°C ~50°C
Operating humidity	5%~95% RH
Display interface	Vertical light bar language
Communication method	Standalone version
Product certification	CE & TUV
IP rating	IP66
Protection function	Protection against overvoltage, undervoltage, overcurrent, leakage, overheating, and surge
Electric leakage protection	Type B 30mA AC & 6mA DC
Dual temperature control protection	Above 85°C, automatic power off after full charge
Operation mode	Touch buttons provided for device-side reservation
Installation mode	Integrated gun and pile design, with a wall mount bracket provided.
Accessories	Gun holder, carrying case, microfiber cloth for cleaning, and pouch for adapter

# EU Standard Portable EV Charger




<b>Country</b>		European EB (The Netherlands, Belgium, and Luxembourg)
<b>Model</b>		Portable
<b>Product Information</b>	<b>Power &amp; current</b>	2.4KW, 8A-10A-13A
	<b>Voltage &amp; frequency</b>	220-240V $\pm$ 10% + 120V
		50 / 60 Hz
	<b>Charging standard</b>	Type 2, IEC 62955
	<b>Protection function</b>	Basic protection: overvoltage/undervoltage protection, overcurrent protection, ground protection, overtemperature protection, leakage protection;
<b>Protection standard</b>	AC30mA+DC6mA	
<b>User Interaction</b>	<b>Communication protocols</b>	Ocpp1.6J+
	<b>Connection mode</b>	Bluetooth 5.2+4G LTE CAT (with SIM card slot)
	<b>Power feed method</b>	Plug-and-charge, APP+RFID
	<b>Interaction</b>	APP+OLED 1.3"1 start button
<b>Product features</b>	<b>RFID function</b>	Supported
		Remote start - stop
		Charging completion reminder and notification for failed gun insertion in reservation mode
		Monthly charging data and comparisons (bar chart)
<b>Product characteristics</b>	<b>IP rating</b>	IP66
	<b>Operating altitude, temperature, and humidity</b>	Altitude <2000m; temperature -30° C~+50° C; humidity 5 %~95%
	<b>Storage temperature</b>	-40°C ~ +60°C
	<b>Installation mode</b>	Portable
	<b>Cable length</b>	5m
<b>Product certification</b>	<b>Certifications</b>	TUV-CE


- 4G & Bluetooth Connection
- GPS Function
- Charging Data and OTA Available
- OCPP1.6J



# OCEAN SUPPLY CHAIN GROUP

 <https://oceanlinking.co.uk>

 [agencyola78@gmail.com](mailto:agencyola78@gmail.com)     [yuanuting@oceanscm.com](mailto:yuanuting@oceanscm.com)

 WhatsApp:+86 13375172445     Line:+ 66 63 740 2510

 Suzhou Industrial District   Suzhou China